



SIGN SPACING = X (feet)		
RuralHighways	60/65 MPH	1000′+-
RuralRoads	45/55 MPH	500′+-
RuralRoads & Urban Arterials	35/40 MPH	350′+-
RuralRoads, Urban Streets Residential & Business Districts	25/30 MPH	200′+-
Urban Streets	25 MPH or LESS	100'+-
ALL SIGNS ARE 48" × 48" BLACK ON ORANGE UNLESS OTHERWISE DESIGNATED.		

GENERAL NOTES

- 1. ALL SIGNS AND SPACING SHALL CONFORM TO THE MUTCD AND CITY OF TUKWILA SPECS.
- 2. PRIORITY PASSAGE THROUGH WORK AREA FOR EMERGENCY VEHICLES SHALL BE PROVIDED AT ALL TIMES.
- 3. ALERT METRO TRANSIT 5 DAYS IN ADVANCE (IF APPLICABLE)
- 4. PROTECTIVE VEHICLE RECOMMENDED-MAY BE A WORK VEHICLE
- 5 DEVICES SHALL NOT ENCROACH INTO ADJACENT LANES.
- 6. ALL SIGNS 48" X 48" B/O UNLESS OTHERWISE SPECIFIED.
- 7. CHANNELIZATION DEVICES ARE 28" REFL. CONES. (see TABLE 1 for spacing distances).
- 8. ALL SPACING MAY BE ADJUSTED TO ACCOMMODATE AT GRADE INTERSECTIONS AND/OR DRIVEWAYS.

Gordon Lee

Project Manager

Road Construction Northwest, Inc.

2500 East Valley Road, Suite C-3, Renton, WA 98057. PO Box 188, Renton WA 98057 Tel 425-254-9999 Ext. 22 Fax, 425-254-1334, Cell 425-531-0104 gordon@rcnw.com

